

may be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
THRIFT DRAIN CLEANER

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Manufacturer's Name

JR2D INC.

Emergency Telephone Number

1-800-255-3924

Address (Number, Street, City, State, and ZIP Code)

Telephone Number for Information

204 South Jackson

409-327-5723

Livingston, Tx. 77351

Date Prepared

2-1-90

Signature of Preparer (optional)

P. K. R. S. S. S.

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Caustic Soda-Sodium Hydroxide	2	2	None	99

Section III — Physical/Chemical Characteristics

Boiling Point	F-2530	Specific Gravity ($H_2O = 1$)	2.13
Vapor Pressure (mm Hg.)	20	Melting Point	F-590
Vapor Density (Air = 1)	Air=1	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water % 100			

Appearance and Odor

White - Solid - No Odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Deg. F None None	None	N/A	N/A

Extinguishing Media This material is not combustible. Contact with water may generate enough heat to ignite combustible materials.

Special Fire Fighting Procedures

None

Unusual Fire and Explosion Hazards This material melts at 590 deg. F. Hot molten material will react violently with water. It will react with metals such as Aluminum, Tin, and Zinc to produce flammable Hydrogen Gas.