

(000000-000000- -5496)

DATE OF ISSUE
1/28/2004SUPERSEDES
8/20/2001

SECTION I - GENERAL INFORMATION

Chemical Name & Synonyms

N/:

Trade Name & Synonyms

TEL-X PLUS AEROSOL

Chemical Family:

Formula Mixture --> X

AEL TELOMER LUBRICANT

Manufacturer's Name:

CHEMSEARCH DIV. OF NCH CORP.

Address:

BOX 152170

IRVING, TX 75015

Prepared By:

L Boynton/Chemist

Product Code Number

5496

Emergency Phone Number

800-424-9300

SECTION II - HAZARDOUS INGREDIENTS

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Chemical Name (Ingredients)

POLYTETRAFLUOROETHYLENE

PROPANE

ISOBUTANE

ISOPROPYL ALCOHOL

Hazard

TLV

PEL

STEL

CAS #

IRRITANT

N/E 1.

N/E 2.

N/E

9002-84-0

FLAM/ASEHX

2500 PPM 1

1000 PPM 2

N/E

74-98-6

FLAM/ASPHX

N/E 1.

N/E 2.

N/E

75-28-5

FLAM/IRR

200 PPM 1

400 PPM 2

400 PPM 1

67-63-0

SECTION III - PHYSICAL DATA

Boiling Point (F):

180°

Specific Gravity (H2O=1):

0.69

Vapor Pressure (MM HG):

1312

Color:

WHITE

Vapor Density (Air=1):

1.9

Odor:

ALCOHOL

PH @ 100%:

4-6

Clarity:

CLOUDY

Evaporation Rate by Volume:

97-98

Evaporation Rate (BU A/C=1):

51.56

Hazardability:

APPRECIABLE

Viscosity:

NON-VISCOUS

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point

53°F / SETAFLASH

Flammable Limits

PRODUCT MIXTURE

LEL

1.8%

UEL

12.7%

Extinguishing Media

X <--Foam X <--Alcohol Foam X <--CO2 X <--Dry Chemical X <--Water Spray <--Other

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. EXTINGUISHING MEDIA SHOULD BE CHOSEN BASED ON THE NATURE OF THE SURROUNDING FIRE. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO DISTANT SOURCES OF IGNITION AND FLASHBACK. FLAME EXTENSION IS >30 INCHES, BURNBACK IS 0 INCHES.

Aerosol Level (NEPA 30B):

3

NEPA 704 Hazard Rating

(0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

2 <--Health 4 <--Flammability 0 <--Instability <--Special

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:

-Acute (Short Term Exposure)

EYE CONTACT: CAUSES SEVERE IRRITATION SEEN AS REDNESS, TEARING, AND A BURNING SENSATION. MAY CAUSE TISSUE DAMAGE.

SKIN CONTACT: CAUSES IRRITATION SEEN AS ITCHING AND REDNESS.

INHALATION: CAUSES RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM

EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND

MAY BE FATAL. INHALATION OF FLUORINE COMPOUNDS RELEASED AS DECOMPOSITION PRODUCTS MAY CAUSE LUNG IRRITATION AND PULMONARY EDEMA. INHALATION OF FUMES

OR SMOKE FROM OVERHEATED OR BURNING PRODUCT MAY CAUSE POLYMER FUME FEVER, A TEMPORARY FLU-LIKE ILLNESS ACCOMPANIED BY FEVER, CHILLS, AND COUGHING.

INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO

ATTENTION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL.

-Chronic (Long Term Exposure)

REPEATED EPISODES OF POLYMER FUME FEVER MAY CAUSE LUNG DAMAGE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS.

TARGET ORGANS: CENTRAL NERVOUS SYSTEM AND LUNGS.

Primary Routes of Entry:

X <--Inhalation

<--Ingestion

<--Absorption

Emergency and First Aid Procedures:

SECTION V - HEALTH HAZARD DATA (Continued)

-Inhalation:

REMOVE FROM THE AREA TO FRESH AIR.. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

-Eye Contact:

IMMEDIATELY RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HOLD THE EYELIDS APART TO ENSURE RINSING OF THE ENTIRE SURFACE OF THE EYES AND LIDS WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

-Skin Contact:

WASH AFFECTED AREAS WITH LARGE AMOUNTS OF SOAP AND WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE.

-Ingestion:

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON.

-Notes to Physician:

THERE IS NO SPECIFIC ANTIDOTE. TREAT THE PATIENT SYMPTOMATICALLY. ACTIVATED CHARCOAL MIXTURE MAY BE BENEFICIAL. SUSPEND 50 G ACTIVATED CHARCOAL IN 400 ML WATER AND MIX WELL. ADMINISTER 5 ML/KG, OR 350 ML FOR AN AVERAGE ADULT. DEPENDING ON THE AMOUNT INGESTED AND RETAINED AS WELL AS THE TOXICITY OF THE PRODUCT, GASTRIC LAVAGE SHOULD BE CONSIDERED. KEEP PATIENT'S HEAD BELOW HIPS TO PREVENT PULMONARY ASPIRATION. IF COMATOSE, A CUFFED ENDOTRACHEAL TUBE WILL PREVENT ASPIRATION.

SECTION VI - TOXICITY INFORMATION

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

IARC--> No NTP--> No OSHA--> No ACGIH--> No OTHER--> No

VOC CONTENT: 98.1% BY WEIGHT; 99.3% BY VOLUME; 676.6 G/L

POLYTETRAFLUOROETHYLENE

NO TOXICITY DATA AVAILABLE

PROPANE

NO TOXICITY DATA AVAILABLE

ISOBUTANE

IHL-RAT LC50: 57 PPH/15M 3.

NO APPARANT ILL EFFECTS IN BREATHING CONCENTRATIONS OF 5% FOR 2 HOURS. 4.
CAUSES DROWSINESS IN SHORT TIME IN CONCENTRATIONS OF 1%. 4.

ISOPROPYL ALCOHOL

IHL-RAT LC50: 16000 PPM/8H 3.

ORL-HMN LDLo: 3570 MG/KG 3.

ORL-RAT LD50: 5045 MG/KG 3.

SKN-RBT LD50: 12800 MG/KG 3.

SKN-RBT SDT: 500 MG MILD 3.

EYE-RBT SDT: 10 MG MODERATE 3.

SECTION VII - REACTIVITY DATA

Stability: X <--Stable <--Unstable

Conditions to Avoid:

AVOID HEAT, HOT SURFACES, SPARKS, AND OPEN FLAMES.

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE; ALDEHYDES, ALKANOLAMINES, AMINES, BASES, AND CHLORINATED COMPOUNDS.

Hazardous Decomposition Products:

OXIDES OF CARBON; CARBONYL FLUORIDE AND HYDROGEN FLUORIDE.

Hazardous Polymerization:

<--May Occur X <--Will Not Occur

Conditions to Avoid:

N/A

SECTION VIII - SPILL OR LEAK PROCEDURES

Steps to be Taken if Material is Released or Spilled:

DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, ELIMINATE IGNITION SOURCES OF ELECTRICAL, STATIC, OR FRICTIONAL SPARKS. WEAR APPROPRIATE PROTECTIVE CLOTHING, VENTILATE THE AREA, ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. USE CARE AS SPILLS MAY BE SLIPPERY.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. TYPICAL DISPOSAL IS TO WRAP THE EMPTY AEROSOL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN THE TRASH. AEROSOL RECYCLING PROGRAMS ARE AVAILABLE IN MANY AREAS. DO NOT PUNCTURE OR INCINERATE THIS CONTAINER.

Neutralizing Agent:

N/A

SECTION IX - SPECIAL PROTECTION INFORMATION

Required Ventilation:

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF MISTS OR VAPORS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSI

SECTION IX - SPECIAL PROTECTION INFORMATION (Continued)

88.2-1992.

Glove Protection:

NEOPRENE OR NITRILE RUBBER GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:

SAFETY GLASSES OR GOGGLES SHOULD BE WORN WHEN HANDLING. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:

WEAR GENERAL-DUTY WORK CLOTHES AND SHOES. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

SECTION X - STORAGE AND HANDLING INFORMATION

Storage Temperature: Indoors--> X Outdoors--> Heated--> Refrigerated-->
Minimum Temperature: 35°F Maximum Temperature: 120°F

Precautions to be Taken in Handling and Storing:

USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY, AND OPEN FLAME. ALWAYS STORE MATERIAL IN ITS ORIGINAL CONTAINER. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

SECTION XI - REGULATORY INFORMATION

Chemical Name	CAS Number	Upper % Limit
None		

Those ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer.

This MSDS is not intended for users in the state of California.

SECTION XII - REFERENCES

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2003.
2. OSHA PEL.
3. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFOWeb, 2003.
4. OSHA'S MSDS.

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPTED FROM LISTING.

-----IRR: IRRITANT, FLAM/FLAMM: FLAMMABLE, COMB: COMBUSTIBLE.
COR: CORROSIVE, CARC: CARCINOGENIC, TOX: TOXIC, N/A: NOT APPLICABLE, N/E: NOT ESTABLISHED, COC: CLEVELAND OPEN CUP, FMCC: PENSKY-MARTIN CLOSED CUP, TCC: TAGLIABUE CLOSED CUP, LEL: LOWER EXPLOSION LIMIT, UEL: UPPER EXPLOSION LIMIT, NFPA: NATIONAL FIRE PROTECTION ASSOCIATION, IARC: INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP: NATIONAL TOXICOLOGY PROGRAM, OSHA: OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV: THRESHOLD LIMIT VALUE, PEL: PERMISSIBLE EXPOSURE LIMIT, STEL: SHORT-TERM EXPOSURE LIMIT, MLD: MILD, MOD: MODERATE, SEV: SEVERE, MUT: MUTAGENIC, ASPHYX: ASPHYXIANT, PNOS: PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, SDT: STANDARD DRAIZE TEST, ORL: ORAL, IHL: INHALATION, HMN: HUMAN

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.