


#029

Flammable Pad Cement



Capitol's 029 Solvent Based, Flammable Carpet Pad Cement is specially formulated to quickly and permanently bond most residential and commercial carpet padding. 029 is fast setting and water proof. 029 allows for stretching of carpet without carpet cushion wrinkling and slippage.

Description: Flammable Carpet Pad Cement

Flammability: Extremely Flammable

Open Time: 10 minutes - Completely dry within 25 minutes.

Clean Up: Safety solvent or mineral spirits.

Shelf Life: One year in closed container.

Limitations: Freeze Proof

Packaging: 1 Gallon (6/case)

Estimated Coverage: 700 lineal feet per gallon

For The Installation Of:

- Rebond Urethane • Prime Urethane • Frothed Urethane • Sponge Rubber • Foam Rubber
- Hair & Jute • Synthetic Hair & Jute

For Use Over:

- Concrete- above, on and below-grade, indoors in the absence of excessive moisture, hydrostatic pressure and alkali • Plywood
- APA Grade Particle Board • OSB • Terrazzo
- Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlayment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Application: Remove cap, punch hole (or holes) in inner seal. Spread a continuous 1/2" bead over the clean, dust free floor in a zigzag motion. Adhesive should be spread around the perimeter, and under all padding seams and throughout the field. Allow adhesive to "tack up" 5-10 minutes and press in padding. Bond is complete in about 30 minutes. Replace cap for storage. **CLEAN UP:** Use a safety solvent or mineral spirits.

First Aid: Skin- Soap and water. Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation- If affected, remove individual to fresh air. Use only in well ventilated areas.

Caution: EXTREMELY FLAMMABLE! Use only in well ventilated areas. Do not use around sources of ignition such as open flames, pilot lights, etc. Do not store at temperatures above 120° F, or in direct sunlight. Do not incinerate container. Wrap empty container and put in trash collections. **KEEP OUT OF REACH OF CHILDREN**



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

#029

Flammable Pad Cement

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd., Dalton, GA 30720
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Neoprene Rubber Adhesive in Solvent Solution
DOT Hazard Classification: None
Product Identity: #029 Flammable Carpet Pad Cement

SECTION II - HAZARDOUS COMPONENTS

	% (weight)	PEL	TLV
Hexane (CAS# 110-54-3)	35	500 ppm	50 ppm
Lacolene (CAS# 64742-89-8)	24	400 ppm	400 ppm
Methyl Ethyl Ketone (CAS# 78-93-3)	8	300 ppm	200 ppm

SARA TITLE III Reportable: Methyl Ethyl Ketone and n-Hexane Lacolene

SECTION III - PHYSICAL DATA

Initial Boiling Point: 149°F. Vapor Pressure: 125.0 mm Hg @ 68°F. Vapor Density (Air=1.0): 3.0. Specific Gravity: 0.77. Percent Volatiles: 70.4%. G/L VOC (Calculated): 542.0.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: <0°F. Explosive Limit (Product): 1.2%. Extinguishing Media: Foam, CO2, Dry Chemical. HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials: carbon dioxide and carbon monoxide, hydrogen chloride, phosgene, various hydrocarbons, etc. SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to keep fire-exposed containers cool until fire is out. Wear self contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. UNUSUAL FIRE & EXPLOSION HAZARDS: Never use welding or cutting torch on or near cans (even empty) because resultant pressure could rupture. Empty cans should be incinerated.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: 300 ppm. Threshold Limit Value: 50 ppm. EFFECTS OF EXPOSURE: Eyes- Can cause irritation, redness, tearing, blurred vision. Skin- Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. Breathing- Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and even asphyxiation. First Aid: Skin- Soap and water. Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. In-

halation- If affected, remove individual to fresh air. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: None. Hazardous Decomposition: None. Hazardous Polymerization: Cannot Occur. Conditions To Avoid: Extreme Heat. Open Flames.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to hood. Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood duct work. Dispose of remaining material in accordance with applicable regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Adequate ventilation is essential to prevent vapor build-up. Open all available windows and entrances to insure good ventilation. RESPIRATOR PROTECTION: Adequate ventilation is normally sufficient. If eyes begin to water or dizziness or headaches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. PROTECTIVE GLOVES: Wear protective gloves to prevent skin contact. EYE PROTECTION: Wear glasses or protective goggles to avoid splashes. OTHER PROTECTIVE EQUIPMENT: None required. WASH HANDS THOROUGHLY WITH SOAP AND WATER.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter. KEEP OUT OF REACH OF CHILDREN.

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com