



## MATERIAL SAFETY DATA SHEETS (MSDS) On-Line OSHA-Required Health And Safety Information!

### Section 1

#### MATERIAL SAFETY DATA SHEET # 92

#### Hercules PVC Cement- Clr, Med Body, Med Set, "LOW VOC"

Date Prepared: 04-Nov-96

Last Reviewed: 01-Jul-98

Hercules Chemical Co,  
Inc.111 South Street  
Passaic, NJ 07055-7398

Tel (800) 221-9330

Fax (800) 333-3456

E-Mail [info@herchem.com](mailto:info@herchem.com)

Meets OSHA 29 CFR 1910.1200

### Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;  
Common Name(s), CAS Numbers)

OSHA PEL    ACGIH TLV    Other Limits

% Upper Bound  
Limits if SARA  
Reportable

*This MSDS is for LOW VOC Product (As shown on label) ONLY. For regular product see MSDS #52*

Tetrahydrofuran (109-99-9)	200 PPM	200 PPM	N/A	--
Methyl Ethyl Ketone (78-93-3)	200 PPM	200 PPM	N/A	35%
Cyclohexanone (108-94-1)	25PPM	25 PPM	N/A	--
Acetone (67-54-1)	750 PPM	750 PPM	N/A	--
N-Methyl Pyrrolidone (872-50-4)	None	None	N/A	15%

**HMIS Hazard Rating:** Health: 3 Flammability: 4 Reactivity: 1 Personal Protection : G

### Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):	Specific Gravity (H <sub>2</sub> O=1):	Vapor Density (Air=1):	Vapor Pressure (mm Hg):
133° Based on first boiling component-acetone.	0.910 ± 0.03	2.0 TO 2.5	190 Based on first boiling component-Acetone.
Melting Point (°F):	Evaporation Rate (Butyl Acetate=1):	Solubility in Water:	
N/A	6-11	55% to 75%	

Appearance And Color: Clear Viscous Liquid

Odor: Ethereal and Acetone-like

---

**Section 4 - Fire And Explosion Hazard Data**

---

**Flash Point:**

0-6°F (TCC) (Based on acetone)

**Flammable Limits:****LEL:**

2%

**UEL:**

13%

**Extinguishing Media:** Dry chemical, Foam, Carbon dioxide**Special Firefighting Procedures:**

Handle as flammable liquid. Wear self-contained breathing apparatus and chemical goggles. Water may be ineffective, but should be used to keep fire-exposed containers cool.

**Unusual Fire And Explosion Hazards:**

Vapor is heavier than air and travels considerable distance to source of ignition and flashback. On long standing may form peroxides which may cause violent reaction especially upon evaporation to dryness.

---

**Section 5 - Reactivity Data**

---

**Stability:** Stable**Conditions To Avoid:** Keep in closed containers away from sparks and open flame.**Incompatibility****(Materials To Avoid):**

Strong oxidizing materials, lithium aluminum hydride, sodium aluminum hydroxide and sodium and potassium hydroxides.

**Hazardous****Decomposition:**CO and CO<sub>2</sub> are formed. Irritating peroxide fumes form when heated to decomposition.**Hazardous****Polymerization:**

Avoid excessive exposure to air and cationic initiators like Lewis Acids.

---

**Section 6 - Health Hazard Data**

---

**Routes of Entry:****Inhalation?** Yes/Primary**Skin?** Yes/Primary**Ingestion?** Yes/Secondary**Health Hazards:**

Corrosive to eyes and skin irritant. Severe overexposure can cause headache, dizziness, and narcosis. May cause dermatosis with prolonged repeated contact.

**Carcinogenicity:****NTP?** NO**IARC?** NO**OSHA Regulated?** NO**Signs And Symptoms of Exposure:**

INGESTION: No effects of exposure expected. INHALATION: Will cause irritation of mucous membranes, nose, eyes, &amp; throat, coughing, difficulty of breathing. Exposure to high vapor concentration may cause headache, dizziness, nausea, narcosis. SKIN CONTACT: Prolonged contact causes common solvent defatting effect. EYE CONTACT: Vapors slightly uncomfortable, splashes irritating. Will cause painful burning or stinging of eyes and lids, watering of eyes and inflammation of conjunctiva.

**Medical Conditions Generally Aggravated By Exposure:**

No data found.

**Emergency And First Aid Procedures:**

INGESTION: Do not induce vomiting. If conscious, dilute by giving 2 glasses of water. Call a physician immediately. INHALATION: Remove to fresh air. If not breathing give artificial respiration preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician. SKIN CONTACT: Wash affected areas with soapy water. Remove contaminated clothing. EYE CONTACT: Immediately

flush eyes with plenty of water for 15 minutes. Consult a physician.

---

## Section 7 - Precautions For Safe Handling And Use:

---

### Steps To Be Taken In Case Material Is Released Or Spilled:

Eliminate sources of ignition. Absorb with sand or inert absorbing material and dispose of with solid waste according to Federal, State and local regulations. Flush spill area with water, avoid flushing into confined areas.

### Waste Disposal Method:

Incinerate in accordance with Federal, State and local regulations.

### Precautions To Be Taken In Handling And Storing:

Store in cool place, well-ventilated area. Keep away from open flame and sources of ignition.

### Other Precautions:

Use normal good personal hygiene.

---

## Section 8 - Control Measures:

---

Respiratory Protection:	In confined spaces or other circumstances where adequate ventilation cannot be assured use NIOSH-approved respirator, positive pressure airline mask, or self contained breathing apparatus.		
Ventilation:	Local	As required.	Special: When using cements in an area of limited ventilation, use a ventilation device such as a fan or air mover to maintain a safe air concentration. N/A -
	Exhaust:	All ventilating devices	
	Mechanical:	must be located so they do not provide a source of ignition.	
Gloves:	PVA gloves.		
Eye Protection:	Chemical safety goggles.		
Other Protective Clothing:	Apron, boots, eye bath, safety shower.		
Work/Hygienic Practices:	Wash thoroughly after handling. Avoid ingestion of the cements. Do not eat or drink when using cements or in the vicinity where such cements are being used.		

---

| [Home Page](#) |

| [MSDS](#) | [Wholesaler Info](#) | [Contractor Info](#) | [Homeowner & Industrial Info](#) |

---

Hercules Chemical Co, Inc.  
111 South Street  
Passaic, NJ 07055-7398  
Tel 1-800-221-9330

Fax 1-973-777-4115

E-Mail [info@herchem.com](mailto:info@herchem.com)

---

*WWW Pages - developed by Hercules Chemical Co. Inc.*

*For more info send E-Mail to [info@herchem.com](mailto:info@herchem.com)*

*©Hercules Chemical Comp., Inc. All Rights Reserved.*