

MATERIAL SAFETY DATA SHEETS (MSDS) On-Line OSHA-Required Health And Safety Information!

Section 1

MATERIAL SAFETY DATA SHEET # 28 Hercules Plumber's Caulk - White

Date Prepared: 14-Sep-89

Last Reviewed: 02-May-01

Hercules Chemical Co, Inc. 111 South Street Passaic, NJ 07055-7398 Tel (800) 221-9330 Fax (800) 333-3456 E-Mail info@herchem.com

Meets OSHA 29 CFR 1910,1200

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;

Comman Name(s), CAS Numbers)

Mineral Spirits (8032-32-4)

OSHA PEL ACGIH TLV Other Limits

400 PPM 500 PPM N/A

% Upper Bound Limits if SARA Reportable

< 3

HMIS Hazard Rating: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: B

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):

Specific Gravity

 $(H_{2}0=1)$:

Vapor Density (Air=1):

Vapor Pressure (mm Hg):

212 (water based)

1.5

> 1

17

Melting Point (°F):

Evaporation Rate (Butyl Acetate=1):

Solubility in Water:

N/A

Soluble

Appearance And Color: White paste

Odor: Mild acrylic & ammonia odor

Section 4 - Fire And Explosion Hazard Data

Flash Point:

Flammable Limits:

LEL:

UEL:

None

N/A

Extinguishing Media: As appropriate for surrounding fire. Non-combustible.

Special Firefighting Procedures:

None

Unusual Fire And Explosion Hazards:

Cured or dried product may give off CO or CO2 if burned.

Section 5 - Reactivity Data

Stability: Stable

Conditions To Avoid: None

Incompatability

None

(Materials To Avoid):

CO or CO2 formed when cured or dried product is burned

Hazardous Decomposition: Hazardous Polymerizatrion:

Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry:

Inhalation? N/A

Skin? YES/Secondary

Ingestion? YES/Secondary

Health Hazards:

None known Carcinogenicity:

NTP? NO

IARC? NO

OSHA Regulated? NO

Signs And Symptoms of Exposure:

Direct eye contact may cause irritation. Prolonged inhalation of vapors can cause irritation of mucous membranes.

Medical Conditions Generally Aggravated By Exposure:

None

Emergency And First Aid Procedures:

SKIN: Wash with soap and warm water. EYES: Flush with water for 15 minutes. Seek medical attention if irritation persists. INGESTION: Do not induce vomiting. Seek medical attention immediately.

Section 7 - Precautions For Safe Handling And Use:

Steps To Be Taken In Case Material Is Released Or Spilled:

Use an absorbent material and sweep up for disposal

Waste Disposal Method:

Small quantities: non-hazardous landfill. Large quantities: Conform to federal, state and local regulations

Precautions To Be Taken In Handling And Storing:

Store between 40 °F and 110 °F

Other Precautions:

None required

Section 8 - Control Measures:

Respiratory Protection:

N/A

Ventilation:

Local Exhaust:

Adequate

Special:

N/A

Mechanical:

N/A

Other:

N/A

Gloves:

Rubber

Eye Protection:

Safety glasses

Other Protective Clothing:

None required

Work/Hygienic Practices:

Use good personal hygiene practices. Wash thoroughly after handling.

Home Page

| MSDS | Wholesaler Info | Contractor Info | Homeowner & Industrial Info |

Hercules Chemical Co, Inc. 111 South Street
Passaic, NJ 07055-7398
Tel 1-800-221-9330
Fax 1-973-777-4115
E-Mail info@herchem.com

WWW Pages - developed by <u>Hercules Chemical Co. Inc.</u> For more info send <u>E-Mail</u> to info@herchem.com
©Hercules Chemical Comp., Inc. All Rights Reserved.