

I. PRODUCT IDENTIFICATION

Trade Name: **TOUCHDOWN #775 SEAM SEALER CEMENT**

Chemical Names, common names: Blend of synthetic resin, rubber and hydrocarbon solvent

Manufacturer's Name: W. F. Taylor Co., Inc.

Address: 11545 Pacific Ave., Fontana, CA 92337

Emergency Phone: (800) 535-5053

Date Prepared: 8/23/00

Business Phone: (909) 360-6677

By: Robert Ddamulira

Preempts Previous MSDS Sheet

H=2 F=4 R=0

II. HAZARDOUS INGREDIENTS

Chemical Names	CAS Numbers	Exposure Limits in Air		
		ACGIH(TLV)	OSHA(PEL)	Percent
Hydrotreated Light Distillate	64810-97-9			35 - 45
Toluene	108-88-3	50 ppm	100 ppm	14 - 20
Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm	17 - 28

WARNING: California Proposition 65: The following statement is made in order to comply with the California State Drinking Water and Toxic Enforcement Act of 1986: *WARNING: This product contains Toluene, a chemical known to cause birth defects or other reproductive harm.*

III. PHYSICAL PROPERTIES

Boiling Point: 165 - 175°F

Density: 6.5 - 7.5

Solubility in water: NIL

Evaporation Rate (nBuAc=1): >1

Vapor Pressure, mmHg at 25c.: N.D.

Vapor Density: >1 (Air =1)

Appearance: Green or clear color, thin syrup consistency

Odor: Mild odor

Volatile Organic Compound (VOC)

Grams VOC/Liter of Coating: 664

Grams VOC/Liter of Material: 664

IV. FIRE AND EXPLOSION

Flash Point, Tag C.C.: 20°F

Auto Ignition Temperature, F: 550°F

Flammable Limits in air, volume %: Lower: 1.2 Upper: 7.0

===== VI. REACTIVITY DATA =====

Stability: X Stable ___ Unstable

Conditions to Avoid: Excessive heat, open flames or sparks

Incompatibility (materials to avoid): None known

Hazardous Decomposition Products (including combustion products): CO, CO2 and other unidentified organic compounds

Hazardous Polymerization: Will not occur.

===== VII. SPILL, LEAK AND DISPOSAL PROCEDURES =====

CAUTION: Material is flammable, eliminate sources of ignition. For large spills, evacuate area. Dike and contain material. Stop leak, if possible. Use water fog to suppress vapor cloud. Use clay or sand to soak up material. Place material in non-leaking container. Cap tightly.

NOTE: *Dispose of all wastes in accordance with federal, state and local regulations.*

===== VIII. SPECIAL HANDLING INFORMATION =====

Ventilation and Engineering Controls: Use local exhaust. Do not use closed air-circulating system. Open windows and doors, if necessary.

Respiratory Protection: None required, unless exposure is over TLV. Use NIOSH approved respirator.

Eye Protection: Chemical goggles or face shield

Gloves: Acrylonitrile gloves

Other Clothing and Equipment: If clothing becomes contaminated, remove and clean before rewearing.

Work Practices, Hygienic Practices: Follow all label instructions.

Other Handling and Storage Requirements: Protect against physical damage. Store in a cool place. Keep away from heat and sparks.

Protective Measures During Maintenance of Contaminated Equipment: No smoking. Avoid sparks. Use respirator, unless exposure is known to be below TLV.

===== IX. LABELING =====

Flammable liquid, fire and explosion hazard. Avoid sparks and flame. Keep out of the reach of children. Do not induce vomiting, if ingested. Avoid breathing build-up of vapors. Use with adequate ventilation.

Fire Extinguishing Media:

☐ Water Spray ☒ Carbon Dioxide ☐ Other

☒ Foam ☒ Dry Chemical

Special Firefighting Procedures: Water may spread burning liquid. Avoid stream of water.

Unusual Fire and Explosion Hazards: Do not expose to excessive heat, open flame or sparks. Turn off all pilot lights.

===== **V. HEALTH HAZARD INFORMATION** =====

Symptoms of Overexposure:

Inhalation: May cause nausea, drowsiness or irritate mucous membrane

Eyes: Vapor may cause eye irritation

Skin: May cause skin irritation and rash

Ingestion: May cause vomiting. Symptoms may be same as inhalation

Health Effects or Risks from Exposure:

Acute: May lead to headache, skin rash and central nervous system depression

Chronic: May cause narcosis, unconsciousness from inhalation. May cause dermatitis from chronic skin contact

First Aid: Emergency Procedures:

Eyes Contact: Wash with water. If irritation persists, seek medical attention.

Skin Contact: Remove from skin and apply skin cream. If irritation persists, see a physician.

Inhalation: Remove to fresh air, administer oxygen. If necessary, seek medical attention.

Ingestion: Seek medical attention. DO NOT induce vomiting, this could cause chemical pneumonitis.

Suspected Cancer Agent:

☒ No

☐ Yes: ☐ Federal OSHA ☐ NTP ☐ IARC ☐ Cal/OSHA

OTHER WARNING: WARNING: This product contains Toluene, a chemical known to cause birth defects or other reproductive harm.

Medical Conditions Aggravated by Exposure: None known

Recommendations to Physician: Determine if emesis should be induced for ingestion.

TAYLOR

#775

TOUCHDOWN

SPECIFICATION SHEET

DESCRIPTION: #775 CARPET SEAM CEMENT NATURAL

#775 is a solvent based adhesive made for edge sealing and edge seaming of all carpets, including sponge-backed and foam rubber-backed carpets. NOT RECOMMENDED FOR VINYL-BACKED CARPETS.

APPLICATION

Cement is ready for use. Pour into a polyethylene squeeze bottle with the side opening spout and apply an 1/8" bead of adhesive to raw primary back or the edge of the side to be seamed. Butt the other piece of carpet to be seamed to the first piece for proper adhesive transfer and to secure the seam. Remove any excess seam cement by rubbing with a clean white rag dampened with Touchdown #9 Clean-Up Solvent. Return unused seam cement to the container. DO NOT STORE SEAM CEMENT IN PLASTIC SQUEEZE BOTTLE.

PHYSICAL PROPERTIES

Base:	Neoprene Rubber
Flammability:	Flammable
Freeze-thaw:	Stable
Color:	Beige
Shelf Life:	One year
Clean-Up:	Touchdown #9 Clean-Up Solvent

DANGER

For professional use only! Extremely flammable! Toxic! Vapors may ignite explosively. Prevent buildup of vapors. Open all windows and doors; use only cross ventilation. Keep away from heat, sparks, and open flame. DO NOT smoke. Extinguish all flames and other sources of ignition during use and until all vapors are gone. Close container after use. KEEP OUT OF REACH OF CHILDREN. Harmful or fatal if swallowed. If swallowed, DO NOT induce vomiting. Call a physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes.

CAUTION

Do not take internally. If swallowed, do not induce vomiting. Call a physician. KEEP OUT OF THE REACH OF CHILDREN.

LIMITED WARRANTY

#775 Carpet Seam Cement is manufactured according to exacting quality control standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product, since the manner and conditions of application are beyond our control.